



Technical data	EB-300	EB-400	EB-6B
Rated pressure:	60kN	120kN	60kN
Stroke:	17mm	42mm	35mm
Oil capacity:	115ml	160ml	115ml
Max crimping:	Cu 300mm <sup>2</sup> /Al 240mm <sup>2</sup>	Cu 400mm <sup>2</sup> /Al 300mm <sup>2</sup>	Cu 240mm <sup>2</sup> /Al 185mm <sup>2</sup>
Cycle time	2.5–3.5s (CU 150 mm <sup>2</sup> )	5–8s (CU 150 mm <sup>2</sup> )	5–6s (CU 150 mm <sup>2</sup> )
Cycles/charger:	Approx. 300 cycles (CU 150 mm <sup>2</sup> )	Approx. 120 cycles (CU 150 mm <sup>2</sup> )	Approx. 350 cycles (CU 150 mm <sup>2</sup> )
Voltage/capacity:	18V/4.0Ah	18V/4.0Ah	18V/4.0Ah
Charging time:	Approx. 80 mins	Approx. 80 mins	Approx. 80 mins
Charging voltage:	AC 100V–240V ;50–60Hz	AC 100V–240V ;50–60Hz	AC 100V–240V ;50–60Hz
Package:	Plastic box	Plastic box	Plastic box
Weight incl. battery:	4.6kgs	7.3kgs	5.5kgs
RSW function: (retract stop for multiple crimps)	×	√	×
<b>ACCESSORIES</b>			
Crimping dies:	16,25,35,50,70,95,120,150,185, 240,300 mm <sup>2</sup>	16,25,35,50,70,95,120,150,185, 240,300 ,400mm <sup>2</sup>	
Battery:	2pcs	2pcs	2pcs
Charger:	1pc	1pc	1pc
Sealing ring of cylinder:	1set	1set	1set
Sealing ring of safety valve	1set	1set	1set