



Technical data	ED-300	ED-400	ED-400U	ED-6B
Rated pressure:	60kN	120kN	120kN	60kN
Stroke:	17mm	42mm	20mm	35mm
Oil capacity:	115ml	160ml	160ml	115ml
Max crimping:	Cu 300mm ² /Al 240mm ²	Cu 400mm ² /Al 300mm ²	Cu 400mm ² /Al 300mm ²	Cu 240mm ² /Al 185mm ²
Cycle time	2.5-5s (Cu 150 mm ²)	5-8s (Cu 150 mm ²)	5-8s (Cu 150 mm ²)	5-8s (Cu 150 mm ²)
Cycles/charger:	Approx. 300 cycles (Cu 150 mm ²)	Approx. 120 cycles (Cu 150 mm ²)	Approx. 130 cycles (Cu 150 mm ²)	Approx. 250 cycles (Cu 150 mm ²)
Voltage/capacity:	18V/4.0Ah	18V/4.0Ah	18V/4.0Ah	18V/4.0Ah
Charging time:	Approx. 80 mins	Approx. 80 mins	Approx. 80 mins	Approx. 80 mins
Charging voltage:	AC 100V-240V ;50-60Hz	AC 100V-240V ;50-60Hz	AC 100V-240V ;50-60Hz	AC 100V-240V ;50-60Hz
Package:	Plastic box	Plastic box	Plastic box	Plastic box
Weight incl. battery:	4.6kgs	7.3kgs	6.2kgs	5.5kgs
RSW function: (retract stop for multiple crimps)	×	√	×	×
ACCESSORIES				
Crimping dies:	16,25,35,50,70,95,120,150,185, 240,300 mm ²	16,25,35,50,70,95,120,150,185, 240,300,400mm ²	16,25,35,50,70,95,120,150,185, 240,300,400mm ²	
Battery:	2pcs	2pcs	2pcs	2pcs
Charger:	1pc	1pc	1pc	1pc
Sealing ring of cylinder:	1set	1set	1set	1set
Sealing ring of safety valve	1set	1set	1set	1set