



HZ-60UNV MANUAL HYDRAULIC MULTI-FUNCTIONAL TOOL







- Flip top style closed working head. The head can rotate 350°
- Two stage hydraulic system
- One head for crimping, cutting and punching
- Safety system inside

Technical data

Working force:	60kN
Stroke:	42mm
Crimping range:	Cu 16-300mm ² Al 10-240mm ²
Cutting range:	Φ40mm for Cu/Al cable and armoured Cu/Al cable.
Punching range:	Φ22.5-61.5mm in the 3.5mm mild steel

ACCESSORIES:

Crimping dies:	16, 25, 35, 50, 70, 95, 120, 150, 185, 240, 300mm ²
Punches&die (Type D):	22.5, 28.3, 34.6, 43.2, 49.6, 61.5mm
Blade:	1 set
Adapter for crimping:	1pc
Adapter for punching:	1pc
3/4", 16UN Draw stud:	1pc
7/16", 20UN Draw stud:	1pc
Spacer:	1pc
Sealing ring of cylinder:	1set
Sealing ring of safety valve:	1set

APPLICATION: CRIMPING	APPLICATION: CUTTING	APPLICATION: PUNCHING
		
		
Cu 16-300mm ² Al 10-240mm ²	Φ40mm for Cu/Al cable and armoured Cu/Al cable.	Φ22.5-61.5mm in the 3.5mm mild steel



HZ-300 SAFETY SYSTEM INSIDE

- Flip top style closed working head. The head can rotate 350°
- Two stage hydraulic system
- Safety system inside, automatic pressure release when crimp is completed.

Technical data

Crimping range:	16-300mm ²
Crimping force:	60kN
Stroke:	17mm
Crimping type:	Hexagon crimping

ACCESSORIES:

Crimping die: 16,25,35,50,70,95,120,150,185,240,300mm²



HZ-400 SAFETY SYSTEM INSIDE

- The tool features with C type head, it can rotate 350°
- Two stage hydraulic system
- Safety system inside, automatic pressure release when crimp is completed.

Technical data

Crimping range:	16-400mm ²
Crimping force:	120kN
Stroke:	42mm
Crimping type:	Hexagon crimping

ACCESSORIES:

Crimping die: 16,25,35,50,70,95,120,150,185,240,300,400mm²