





SHP-430H

- •
- Split crimping head with interchangeable dies Suitable for transmission and distribution of indoor and outdoor projects •
- The tool work for different kind of connecting and building over head cable

Technical data	
Crimping range:	50-400mm ²
Crimping force:	116kN
Stroke:	30mm
Crimping type:	Hexagon Crimping
Accessories:	
Crimping dies:	50,70,95,120,150,185,240,300,400mm ²
Sealing O-ring:	One Set
Note: It Can Match Hand Pump	

SHP-510H

- Split crimping head with interchangeable dies
 Suitable for transmission and distribution of indoor and outdoor projects
- The tool work for different kind of connecting and building over head cable

Technical data	
Crimping range:	50-400mm²
Crimping force:	126kN
Stroke:	38mm
Crimping type:	Hexagon Crimping
Accessories:	
Crimping dies:	50,70,95,120,150,185,240,300,400mm ²
Sealing O-ring:	One Set
Note: It Can Match Hand Pump	





CO-630C

- C Type head, easy for operation.
- Interchangeable dies, both for series JL13 and 12Ton crimping dies.
- Alloy steel forged high strength head.

Remark: The allowable temperature above reference seals, tubing and factory used hydraulic oil temperature range, and should refer to allowable temperature of the hydraulic pump as well.

Technical data	
Crimping force:	142kN
Stroke:	50mm
Rated pressure:	70MPa
Crimping range:	Cu cable:16-630mm², Al cable:10-500mm²
	Steel core aluminum stranded wire (LGJ):35-240mm
Temperature:	-20°C-50°C
Weight :	7.4kg (with one die set)
Size:	400X64X110mm