



Technical data	ED-55
Cutting force:	120kN
Stroke:	58mm
Hydraulic Oil:	Shell Tellus T15# S2V HV15
Cutting range:	≤φ55mm
Armoured cable	φ55mm
ACSR:	φ52mm
Cu/Al cable:	φ55mm
Steel strand:	φ20mm
Wire rope:	φ25mm
Size of tool:	458x354x83mm
Voltage/capacity:	DC 18V/4.0Ah
Charging time:	80 mins
Package:	Plastic box
Accessories:	
Battery:	2pcs
Charger:	1pc
Sealing ring of cylinder:	1set
Sealing ring of safety valve:	1set



Technical data	ED-45	ED-85	ED-105
Cutting force:	60kN	60kN	120kN
Stroke:	50mm	86mm	108mm
Cutting range:	φ45mm	φ85mm	φ105mm
Type of cable:	Cu/Al cable	Cu/Al Cable, light weight armoured Cu/Al cable(depending on cable type)	
Voltage/capacity:	18V/4.0Ah	18V/4.0Ah	18V/5.0Ah
Charging time:	80 mins	80 mins	100 mins
Charging voltage:	AC 100V~240V ;50~60Hz	AC 100V~240V ;50~60Hz	AC 100V~240V ;50~60Hz
Package:	Plastic box	Plastic box	Plastic box