



Technical data	BZ-65C	BZ-85C	BZ-105C	BZ-120C
Output force:	60kN	60kN	150kN	150kN
Stroke:	50mm	50mm	70mm	70mm
Cutting range	φ65mm (Cu/Al cable)	φ85mm (Cu/Al cable)	φ105mm (Cu/Al cable and Cu/Al armoured cable)	φ120mm (Cu/Al cable and Cu/Al armoured cable)
Voltage/capacity:	18V/4.0Ah	18V/4.0Ah	18V/5.0Ah	18V/5.0Ah
Charging time:	80 mins	80 mins	100 mins	100 mins
Accessories				
Battery:	2pcs	2pcs	2pcs	2pcs
Charger:	1pc	1pc	1pc	1pc
Sealing ring of cylinder:	1set	1set	1set	1set
Sealing ring of safety valve:	1set	1set	1set	1set

 ✓
 Cu/Al Cable

 ×
 ACSR

 ✓
 Armoured Cable

 ×
 Steel bar



Technical data	BZ-55
Cutting force:	120kN
Stroke:	58mm
Hydraulic Oil:	Shell Tellus T15# S2V HV15
Cutting range:	≤φ55mm
Armoured cable	φ55mm
ACSR:	φ52mm
Cu/Al cable:	φ55mm
Steel strand:	φ20mm
Wire rope:	φ25mm
Size of tool:	452x404x85mm
Voltage/capacity:	DC 18V/4.0Ah
Charging time:	80 mins
Package:	Plastic box
Accessories:	
Battery:	2pcs
Charger:	1pc
Sealing ring of cylinder:	1set
Sealing ring of safety valve:	1set

