



CPC-85B

- Flip top cutting head, easy for operation, more convenient
- The blade guide block design effectively prevents blade dislocation during cutting procession can be matched with any pump

Technical data

Cutting force:	60kN
Cutting range:	Telephone cable:φ85mm Armoured Cu/Al cable:φ50mm
Length:	465mm
Weight:	7.9kg

CPC-65C/85C/105C/120C

- Opening C type cutting head.
- Hydraulic quick coupler connect with the pump for working.
- Guide pad design to avoid the blade dislocation during cutting procession.

Technical data

Item No:	CPC-65C	CPC-85C	CPC-105C	CPC-120C
Armoured Cu/Al cable:			φ105mm	φ120mm
Cu/Al cable:	φ65mm	φ85mm	φ105mm	φ120mm
Rated output:	60kN	60kN	140kN	140kN
Rated pressure:	63Mpa	63Mpa	66MPa	66MPa
Oil capacity:	50ml	50ml	150ml	150ml
Max. pressure:	70Mpa			
Retraction mode:	Piston retraction			
Hydraulic oil:	Shell Tellus T15			
Working Temperature:	-20°C-50°C			
Cable:	Cu/Al cable, armoured Cu/Al cable			



CPC-100B

- Suggest to match with CP-390, CP-700

Technical data

Cutting force:	60kN
Cutting range:	Telephone cable:φ100mm Armoured Cu/Al cable:φ75mm
Length:	505mm
Weight:	8.4kg

CPC-105B

- Suggest to match with CP-390, CP-700

Technical data

Cutting force:	120kN
Stroke:	108mm
Cutting range:	φ105mm Cu/Al cable and armoured cable
Length:	445mm