



Technical data	HH-65C	HH-85C	HH-105C	HH-120C
Output force:	60kN	60kN	150kN	150kN
Stroke:	50mm	50mm	71mm	71mm
Max cutting diameter:	φ65mm Cu/Al cable	φ85mm Cu/Al cable	φ105mm Cu/Al cable and armoured cable	φ120mm Cu/Al cable and armoured cable
Working temperature:	-10°C-50°C			
Voltage/capacity:	AC 220V 50/60Hz (Optional AC 110V 50/60Hz)			
Rated output	520W			
Weight:	6.5kgs	6.8kgs		
Accessories				
Cylinder Sealing ring	1set	1set	1set	1set
Safety valve Sealing ring	1set	1set	1set	1set
	✓	✗	✓	✗
	Cu/Al Cable	ACSR	Armoured Cable	Steel bar



Technical data	HH-55
Output force:	120kN
Stroke:	58mm
Hydraulic oil	Shell Tellus T15
Cutting range:	≤φ55mm
Armoured Cable	≤φ55mm
ACSR	≤φ52mm
Cu/Al cable	≤φ55mm
Steel strand	≤φ20mm
Wire rope	≤φ25mm
Package:	Plastic box
Size:	425x360x83mm
Accessories	
Cylinder Sealing ring	1set
Safety valve Sealing ring	1set

