



CP-700B

- Hydraulic operated pump to drive crimping head, Cutting head, punching head and cylinders
- The tool comes with the pressure 700kg/cm²
- With 2m high pressure oil hose and PT 3/8" screw thread

Technical data

Max output pressure :	High pressure: 70Mpa
	Low pressure: 2Mpa
Capacity of oil:	1800cc
Output of the oil:	High pressure: 1.8cc
	Low pressure: 10cc
Type:	Hand

TFP-800

- Hydraulic foot pump to drive crimping head, cutting head, punching head and cylinders
- The tool comes with the pressure 700kg/cm²,
- Safety valve inside to prevent overload
- With 2m high pressure oil hose and PT 3/8" Screw thread

Technical data

Max output pressure :	70Mpa
Capacity of oil:	850cc
Measurement (LxWxH):	450x150x200mm
Type:	Foot



TEP-700B

Technical data

Working Power:	AC220V 50HZ
Power Rating:	0.75 kw
Nominal delivery capacity:	Low pressure 4L/min
	High pressure 0.5L/min
Max working pressure:	70Mpa
Oil capacity:	2L
Weight:	17KG
External size:	210x210x340
Hydraulic oil :	HV15 hydraulic oil
Speed:	20000r/min

ZCB6-6

HALF CLOSED STYLE

Technical data

Rated output:	70Mpa
Motor voltage:	220V/380V
Motor power:	750W
Rate of output:	High: 0.7/min
	Low: 5L/min
Oil capacity:	8L
Speed:	1400r/min
Weight:	22KG
Size:	30x24x38cm