

SL-2620

Battery Powered Axial Press Tool

For axial press air conditioner pipe
 Be used in air conditioner, heating, refrigeration system

Specifications

Rated pressure:	26kN
Connecting range:	φ6.35-28.6mm copper pipe
Charging voltage:	AC 100V~240V ;50~60Hz
Charging time:	Approx.40mins
Hydraulic oil:	35ml
Stroke:	20mm
Service interval:	10000cycles
Voltage of battery:	DC 18V,2.0Ah
Ambient temperature:	-10°C~40°C
Weight:	
Tool size:	331x130x76mm

Accessories:

Connecting jaws(optional):	6.35、9.52、12.7、15.88、19.05、 22.2、25.4、28.6mm (Integral type)
Battery:	2 pcs
Charger:	1 pc
Sealing ring of cylinder:	1 set
Sealing ring of safety valve:	1 set



SL-4523

Battery Powered Axial Press Tool

For axial press air conditioner pipe
 Be used in air conditioner, heating, refrigeration system

Specifications

Rated pressure:	45kN
Stroke:	23mm
Connecting range:	Φ6.35-38.1mm copper pipe
Hydraulic oil:	35ml
Ambient temperature:	-10°C~40°C
Service interval:	10000cycles
Voltage of battery:	DC 18V,2.0Ah
Charging voltage:	AC 100V~240V ;50~60Hz
Charging time:	Approx.40mins
Tool size:	347x155x76mm

Accessories:

Connecting jaws(optional):	6.35, 9.52, 12.7, 15.88, 19.05, 22.2, 25.4, 28.6, 31.8, 34.9, 38.1mm
Battery:	2 pcs
Charger:	1 pc
Sealing ring of cylinder:	1 set
Sealing ring of safety valve:	1 set

